



ANTIQUING AGENT

SECONDARY COLORANT FOR STAMPED CONCRETE

DESCRIPTION

ANTIQUING AGENT is a colorant composed of specially blended iron-oxide pigments. When applied to stamped concrete or THIN-CRETE it provides a rich and unique accent.

PRIMARY APPLICATIONS

ANTIQUING AGENT is specifically designed for use with stamped concrete or THIN-CRETE, but may be used to highlight any properly prepared concrete surface prior to sealing.

FEATURES/BENEFITS

ANTIQUING AGENT provides a beautiful accent to freshly stamped concrete or THIN-CRETE but is also the perfect product to revitalize old stamped concrete. These colorants are specially designed to tint grout lines and stamped impressions without affecting the base color. There are various combinations of colors that will give the antiquing effect by accentuating the highlights, and making stamped patterns come to life.

TECHNICAL INFORMATION

ANTIQUING AGENT is composed of light-fast, UV-stable, iron-oxide pigments and will not fade.

Available in all 30 standard colors (see Increte Standard Color Charts). Special colors can be matched by request (minimum order requirements apply).

PACKAGING

ANTIQUING AGENT is available in 5 lb (2.26 kg) units.

SHELF LIFE

4+ Years in original, unopened container.

COVERAGE

Depending upon desired effect, approximately 150 to 200 ft² per mixed gallon (3.65 to 4.9 m² per mixed liter).

DIRECTIONS FOR USE

APPLICATION PROCESS

PREPARATION: All surrounding areas should be protected from contamination by overspray or run-off colorant. Paper or other absorbent material is recommended for masking.

SURFACE PREPARATION: After THIN-CRETE has been stamped and allowed to dry overnight, the surface must be acid washed to remove any residual release agent and open up the surface for absorption of the colorant. 10 Parts water to 1 part muriatic acid is recommended.

MIXING PROCEDURE: ANTIQUING AGENT is highly concentrated. Add approximately 1 to 2 tablespoons (5 oz/gal or 37 g/L) of water and mix manually or shake until evenly dispersed. Note: more or less colorant may be used to achieve the desired effect. Mix only enough for use in one application because pigment may settle.

APPLICATION: For best results apply colorant solution with a pump sprayer. Allow colorant to dry completely (approximately 24 hours), then seal with a cure-and-seal to protect the surface.

CLEAN-UP

Clean hands, tools and equipment with soap and water.

PRECAUTIONS/LIMITATIONS

- A test area is recommended to assure the desired appearance.
- Do not allow applied product to pond.
- Dry colorant is an irritant to eyes and skin.
- Wear rubber gloves and splash-proof goggles.
- For professional use only.
- In all cases, consult the Safety Data Sheet before use.

Rev. 08.15

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.